

## FAAC-KIT-770-24V



### 770 24V SWING ARM GATE DOUBLE KIT FOR GATES UP TO 3.5M

FAAC 770 24V KIT for a pair of residential swing gates up to a maximum of 3.5m each leaf.

#### FEATURES

- Protection class: IP67
  - To “initialise” the automated system, just carry out the SET-UP operation, selecting a suitable dipswitch
  - The following parameters are automatically self-learned during this operation:
    - Opening/closing times
    - Pause time
    - Traction/thrust force
    - Deceleration at end of opening and closing
  - Soft start (starting at gradual speed)
  - Continuously controlled electronic clutch, active at both opening and closing
  - Four sensitivity levels
  - Movement reversed in case of an obstacle
  - Emergency stop function (if clutch operates for two consecutive cycles)
  - Emergency battery (optional) ensuring operation during a power cut (15 cycles max)
- 
- Kit includes:
    - 2x FAAC 770 24V Electromechanical Operator
    - 2x Underground Foundation box with release System
    - 1x FAAC E024S Control Board
    - 1x Control Board Housing
    - 1x Pair of FAAC XP20B photocells
    - 1x FAAC Plug-in Receiver / Decoder 868 SLH
    - 2x FAAC Two Channel Transmitter 868 SLH