
SPECIALIZED SECURITY PRODUCTS

sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

# RT-BE20/200





## ROGER TECH GEARMOTOR FOR SWING GATES UP TO 2.5M BRUSHLESS

### FEATURES

- Electromechanical actuator BRUSHLESS
- Low voltage
- Super intensive use, with native encoder onboard
- Irreversible
- Ideal for swing gates with leaf up to 2.8m length, with mechanical stopper in opening and closing

### TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 24V
- Power rating: 200W
- Frequency of use: Intensive use
- Thrust: 100 - 2200N
- Operating temperature: -20 C° +55 C°
- Protection level: IP43
- Reductor Type: Irreversible
- Manoeuvre speed: 1.66 cm/s
- Opening time at 90°: 15-25 s
- Stroke: 400 mm
- Limit switch: Mechanical stopper in opening and closing
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Operating cycles per day (opening/closing - 24 hours no stop): 800
- Maximum dimension product in mm (L x W x H): 867 x 105 x 155
- Product weight packed (Kg): 7.9

## RELATED PRODUCTS



RT-BE20/200/HS



RT-MC781



RT-KT206