


## RT-BE20/200



QUICK W	QUICK W	ANGULO
mm	mm	APERTURA
110	100	140°
110	200	90°
130	100	140°
130	200	140°
150	100	140°
150	150	120°
150	200	110°
150	200	140°
180	100	110°
180	150	140°
QUICK W	QUICK W	QUICK W
860 mm	860 mm	mm
100	200	90

## BRUSHLESS MOTOR FOR SWING GATES UP TO 2.8M

Low voltage brushless electromechanical actuator, for super intensive use, with native encoder on board, irreversible, ideal for swing gates with leaves up to 2.8m with mechanical stops on opening and closing.

### FEATURES

- Electromechanical actuator BRUSHLESS
- Low voltage
- Super intensive use, with native encoder onboard
- Irreversible
- Ideal for swing gates with leaf up to 2.8m length, with mechanical stopper in opening and closing

### TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 24V
- Power rating: 200W
- Frequency of use: Intensive use
- Thrust: 100 - 2200N
- Operating temperature: -20 C° +55 C°
- Protection level: IP43
- Reductor Type: Irreversible
- Manoeuvre speed: 1.66 cm/s
- Opening time at 90°: 15-25 s
- Stroke: 400 mm
- Limit switch: Mechanical stopper in opening and closing
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Operating cycles per day (opening/closing - 24 hours no stop): 800
- Maximum dimension product in mm (L x W x H): 867 x 105 x 155
- Product weight packed (Kg): 7.9

## RELATED PRODUCTS



**RT-BE20/200/HS**



**RT-MC781**



**RT-KT206**