SPECIALIZED SECURITY PRODUCTS

sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

RT-BH23/282



ROGER TECH GEARMOTOR FOR SWING GATES WITH ARTIC. SHORT ARMS

Roger Tech Gearmotor for Swing Gates with Artic. Short Arms Brushless

FEATURES

- Electromechanical articulated motor BRUSHLESS
- Low voltage
- Super intensive use, with native encoder onboard
- Irreversible
- Ideal for swing gates with leaf up to 2.8m of length
- With mechanical stopper in opening and closing and with standard version of short arms

TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 24V
- Power rating: 160W
- Frequency of use: Intensive use
- Torque: 50 - 280 N m
- Operating temperature: -20+55° C
- Protection level: IP43
- Reductor Type: Irreversible
- Manoeuvre speed: 1 - 1.9 Rpm
- Opening time at 90°: 12-20 s
- Limit switch: Mechanical stopper in opening and closing
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Operating cycles per day (opening/closing - 24 hours no stop): 1900
- Maximum dimension product in mm (L x W x H): 230 x 190 x 284
- Product weight packed (Kg): 13