

RT-BR21/351



ROGER TECH BRUSHLESS UNDERGROUND MOTOR ONLY WITH 2M CABLE

Roger Tech Brushless Underground Motor Only With 2M Cable

FEATURES

- Electromechanical underground motor, BRUSHLESS
- Low voltage
- Super intensive use, with native encoder onboard
- Irreversible
- Ideal for swing gates with leaf up to 4.5m
- Standard version with 2m cable

TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 24V - 36V
- Power rating: 200W
- Frequency of use: Intensive use
- Torque: 50 - 300 N m
- Operating temperature: -20+55°C
- Protection level: IP67
- Reductor Type: Irreversible
- Manoeuvre speed: 1.2 Rpm
- Opening time at 90°: 19-29 s
- Limit switch: Mechanical stoppers
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Maximum opening: 105°(optional 125° - 360°)
- Power supply cable length: 2m
- Bearing on main shaft: Standard
- Operating cycles per day (opening/closing - 24 hours no stop): 300
- Maximum dimension product in mm (L x W x H): 345 x 224 x 144
- Product weight packed (Kg): 12.8

RELATED PRODUCTS



RT-LT300



RT-LT301



RT-FU100