SPECIALIZED SECURITY PRODUCTS

sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

RT-BR21/351/HS

ROGER TECH GEARMOTOR FOR UNDERGROUND BRUSHLESS HS 2M CABLE

FEATURES

- Electromechanical underground motor, BRUSHLESS HIGH SPEED,
- Low voltage
- Super intensive use, with native encoder onboard
- Irreversible
- Ideal for swing gates with leaf up to 3m
- Standard version with 2m cable

TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 24V - 36V
- Power rating: 200W
- Frequency of use: Intensive use
- Torque: 50 - 200 N m
- Operating temperature: -20+55°C
- Protection level: IP67
- Reductor Type: Irreversible
- Manoeuvre speed: 2 Rpm
- Opening time at 90°: 10-25 s
- Limit switch: Mechanical stoppers
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Maximun opening: 105°(optional 125° - 360°)
- Power supply cable length: 2m
- Bearing on main shaft: Standard
- Operating cycles per day (opening/closing - 24 hours no stop): 1300
- Maximum dimension product in mm (L x W x H): 345 x 224 x 144
- Product weight packed (Kg): 12.8

RELATED PRODUCTS

RT-E80/TX54R/2

RT-LT300

RT-LT301