SPECIALIZED SECURITY PRODUCTS

sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

RT-KIT-BE20/212/HS



ROGER TECH SWING GATES UP TO 2.5M BRUSHLESS HS

Roger Tech Swing Gates up to 2.5m Brushless HS with 2 x BE20/200/HS + 1 x EDGE1/BOX + 1 x H93/RX20/I + 2 x E80/TX52R/2 + 1 x M90/F4ESO + 1 x Signboard

FEATURES

- KIT Electromechanical actuator BRUSHLESS HIGH SPEED
- Low voltage
- Super intensive use, with native encoder onboard
- Irreversible
- Ideal for swing gates with leaf up to 2.5m length, with mechanical stopper in opening and closing

TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 36V
- Power rating: 200W
- Frequency of use: Intensive use
- Thrust: 100 - 2200N
- Operating temperature: -20 C° +55 C°
- Protection level: IP43
- Reductor Type: Irreversible
- Manoeuvre speed: 3 cm/s
- Opening time at 90°: 10-15 s
- Stroke: 400mm
- Limit switch: Mechanical stopper in opening and closing
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Operating cycles per day (opening/closing - 24 hours no stop): 800
- Maximum dimension product in mm (L x W x H): 867 x 105 x 155
- Product weight packed (Kg): 20.3

RELATED PRODUCTS



RT-E80/TX52R/2



RT-KT206



RT-MC781