

## RT-KIT-BE20/410



**ROGER  
TECHNOLOGY**  
PREMIUM DEALER

### BRUSHLESS LOW VOLTAGE DOUBLE SWING GATE KIT UP TO 4M

KIT Low voltage brushless electromechanical actuator, for super intensive use, with native encoder on board, irreversible, ideal for swing gates with leaves up to 4 m with mechanical stops on opening and closing.

#### FEATURES

- KIT Electromechanical actuator BRUSHLESS
- Low voltage
- Super intensive use, with native encoder onboard
- Irreversible
- Ideal for swing gates with leaf up to 4m length, with mechanical stopper in opening and closing

#### TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 36V
- Power rating: 200W
- Frequency of use: Intensive use
- Thrust: 100 - 2800N
- Operating temperature: -20 C° +55 C°
- Protection level: IP43
- Reductor Type: Irreversible
- Manoeuvre speed: 1.66 cm/s
- Opening time at 90°: 17-26 s
- Stroke: 550 mm
- Limit switch: Mechanical stopper in opening and closing
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Operating cycles per day (opening/closing - 24 hours no stop): 1000
- Maximum dimension product in mm (L x W x H): 1019 x 105 x 155
- Product weight packed (Kg): 21

## RELATED PRODUCTS



**RT-E80/TX52R/2**



**RT-KT206**



**RT-MC781**