

RT-KIT-BE20/410



ROGER TECH BRUSHLESS LOW VOLTAGE DOUBLE SWING GATE KIT TO 4M

Roger Tech 36v Brushless Electric Gate Kit - Double 2 x BE20/400, 1 x EDGE1/BOX 1 x M90/F4ESO, 1 x ANT02 2 x Synus/2, 1 x H93/RX20/I

FEATURES

- KIT Electromechanical actuator BRUSHLESS
- Low voltage
- Super intensive use, with native encoder onboard
- Irreversible
- Ideal for swing gates with leaf up to 4m length, with mechanical stopper in opening and closing

TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 36V
- Power rating: 200W
- Frequency of use: Intensive use
- Thrust: 100 - 2800N
- Operating temperature: -20 C° +55 C°
- Protection level: IP43
- Reductor Type: Irreversible
- Manoeuvre speed: 1.66 cm/s
- Opening time at 90°: 17-26 s
- Stroke: 550 mm
- Limit switch: Mechanical stopper in opening and closing
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Operating cycles per day (opening/closing - 24 hours no stop): 1000
- Maximum dimension product in mm (L x W x H): 1019 x 105 x 155
- Product weight packed (Kg): 21

RELATED PRODUCTS



RT-E80/TX52R/2



RT-KT206



RT-MC781