

RT-KIT-SMARTY4/HS



**ROGER
TECHNOLOGY**
PREMIUM DEALER

ROGER TECH FULL SWING GATE OPERATOR KIT WITH 2 X SMARTY 4HS

Roger Tech Full Swing Gate Operator Kit with 2 x Smarty 4HS +
1 x Kit Edge22/UK

FEATURES

- Low voltage
- High speed
- Irreversible
- BRUSHLESS electromechanical gear motor for extremely heavy duty
- For swing gates with gate leaf up to 4m

Kit Composition:

- 1x Edge/1 Digital control board
- 2x Smarty 4/HS Brushless Motor
- 2x E80/TX52R/2 Remote controls
- 1x H93 receiver
- 1x R90/F2ES Photocells
- 1x Fifty Light or Antenna

TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 36V
- Power rating: 200W
- Frequency of use: Intensive use
- Thrust: 600 - 4500N
- Operating temperature: -20 C° +55 C°
- Protection level: IP44
- Reductor Type: Irreversible
- Manoeuvre speed: 2 - 1 cm/s
- Opening time at 90°: 15-25 s
- Stroke: 370mm
- Limit switch: Mechanical stopper in opening and closing
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Operating cycles per day (opening/closing - 24 hours no stop): 1000
- Maximum dimension product in mm (L x W x H): 1162 x 116 x 165
- Product weight packed (Kg): 16.5