SPECIALIZED SECURITY PRODUCTS

sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

RT-SET-R21/353-S



230V SINGLE UNDERGROUND KIT UP TO 3.5M

230v electromechanical underground single kit, ideal for swing gates with leaf up to 3.5m of length. Standard version with 2m cable.

FEATURES

- Electromechanical underground motor 230V AC
- Irreversible
- Ideal for swing gates with leaf up to 3.5 metres of length
- Standard version with 2 meters cable
- Kit Composition:
  1x H70/200ac Controller
  1x R21/351 Brushless Motor
  1x RL650 Release shoe
  1x FU100 Galvanised Foundation Box
  2x E80/TX52R/2 Remote controls
  1x R90/F2ES Photocells
  1x Fifthy Light or Antenna

TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 230V AC
- Power rating: 200W
- Frequency of use: 30%
- Torque: 300 N m
- Operating temperature: -20+55°C
- Protection level: IP67
- Reductor Type: Irreversible
- Manoeuvre speed: 1.2 Rpm
- Opening time at 90°: 19 s
- Motor thermal protection: 150°C
- Limit switch: Mechanical stoppers
- Encoder: Optional as an accessory
- Maximun opening: 105°(optional 125° - 360°)
- Power supply cable length: 2m
- Bearing on main shaft: Standard
- Maximum dimension product in mm (L x W x H): 345 x 224 x 144
- Product weight packed (Kg): 67