
sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

BFT-PCELL-COMPACTA





BFT COMPACTA A20-180 PHOTOCELLS (DESME REPLACEMENT)

FEATURES

Flexibility: COMPACTA may use a wide input power supply range, 12-33Vac 50/60Hz and 15-35Vdc, making it usable in a vast number of installations. In addition, it may be wired to all the BFT control boards with test.

Maximum installation simplicity: the possibility of adjusting the infra-red head up to 90° both left and right (180° in total) means these photocells can be installed on walls or posts that are not aligned, thus saving time and obtaining a clean and seamless installation. On the vertical plane, optics are fixed, although the geometry allows recovering slight misalignments up to +/- 5°. Finally, once the correct angle of the optics is found, the cover locks to the base with a simple click.

TECHNICAL INFORMATION

- Supply voltage: 12 - 33Vac / 15 - 35Vdc
- Nominal Range: 20 m
- Horiz. adjustment: 180 °
- Degree of protection (IP): 44
- Interconnectivity: no

Imperial measurements
The data shown are for information purposes only.

- Supply voltage: 12 - 33Vac / 15 - 35Vdc
- Nominal Range | 65 ft
- Horiz. adjustment: 180 °
- Degree of protection (IP): 44
- Interconnectivity: no