
SPECIALIZED SECURITY PRODUCTS

sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

EM20-ECO





STANDARD MONITORED ECO FRIENDLY MAGLOCK 12/24VDC

FEATURES

HALF THE POWER CONSUMPTION ALL THE HOLDING FORCE

- MOV provides spike and surge protection
- Compatible with existing maglock and associated bracket range
- Fail-safe operation (power to lock)
- Anti-residual magnetism protection
- Top-plate, armature-plate and fixings included
- Dual voltage 12Vdc or 24Vdc (selectable)
- Surface mount & Silver anodised aluminium finish
- Lock monitoring

Recent customer quoted as saying ***"I will ensure that we use the ECO range from now on, the other advantage to us is, as we supply Access control units that control up to 8 doors the total reduction in current is significant and reduces the Power Supply requirements or least means they run cooler and more reliably".***

TECHNICAL INFORMATION

- Holding force: up to 545kg (1200lb)
- Current draw = 250mA @ 12Vdc / 130mA @ 24Vdc
- Voltage tolerance: +/- 5%
- Operating temp: -10°C to +55°C, Humidity: 0-95% non-condensating
- Weight: 4.5kg approx.
- Red/Green LED indicator
- Relay: COM/NO/NC

RELATED PRODUCTS

			
EM500AZLG-DC	**EM500ZL**	**EM02-ECO**	**EM05-ECO**