

BFT-VIRGO-SMART-BT-A-KIT



24V TWIN ARTICULATED KIT SLIDING ARM UP TO 2.5M

The Virgo Smart BT A is a 24v gate operator suitable for a range of different environments and has been designed to be installed easily. The articulated arm, with an optional sliding arm, is one of the most adaptable swing gate operators in the Virgo product family.

FEATURES

- The Virgo Smart BT A is a 24v gate operator suitable for a range of different environments and has been designed to be installed easily.
- The articulated arm, with an optional sliding arm, is one of the most adaptable swing gate operators in the Virgo product family.
- It is possible to install on pillars up to 235mm deep or with limited lateral space, using the articulated arm and sliding arm.
- The Thalia control panel is mounted in a raised position for easier programming and there are a wide-ranging set of features available for a customised installation.
- The Virgo Smart is U-Link compatible.

Included in the kit:

2x Virgo Smart operators
1x Built-in Thalia control panel & receiver
2x Mitto radio transmitters
1x Pair of Compacta 180° photocells
1x 24v Radius light

TECHNICAL INFORMATION

- Power supply: 24V
- Gate leaf length: 2m
- Max leaf weight: 200kg
- Control panel: THALIA
- Cycle time: 14 sec
- Slowdown: Yes
- Locking: Mechanical
- Impact reaction: Electronic torque limiter
- Frequency of use: Semi-intensive
- Protection rating: IP44
- Temperature range: -20°C to 55°C