

RT-BR21/361



BRUSHLESS UNDERGROUND MOTOR 36V WITH 10MT CABLE

Electromechanical underground motor, BRUSHLESS, low voltage, super intensive use, with native encoder onboard, irreversible, ideal for swing gates with leaf up to 4,5 m. Standard version with 10 m cable.

FEATURES

- BRUSHLESS
- Low voltage
- Super intensive use
- Irreversible
- Ideal for swing gates with leaf up to 4,5 m
- Standard version with 10 m cable

TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 24V - 36V
- Power rating: 200W
- Frequency of use: Intensive use
- Torque: 50 - 300 N m
- Operating temperature: -20+55°C
- Protection level: IP67
- Reductor Type: Irreversible
- Manoeuvre speed: 1,2 Rpm
- Opening time: 19-29 s
- Limit switch: Mechanical stoppers
- Recommended digital controllers: 230V: EDGE1/BOX - 115V: EDGE1/BOX/115
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Maximum opening: 105°(optional 125° - 360°)
- Power supply cable length: 10m
- Bearing on main shaft: Standard
- Operating cycles per day (opening/closing - 24 hours no stop): 1300
- Maximum dimension product in mm (L x W x H): 345 x 224 x 144
- Product weight packed (Kg): 14.2
- Number items per pallet: 50