

## GIBIDI-29200ES



### TOP 291S EVO (FAST) OPERATOR

TOP 291 EVO, 230Vac, gate mounted hydraulic ram without hydraulic slowdowns. Operator only.

#### FEATURES

- NEW die-cast aluminium flange and oversized tie rods.
- NEW fully integrated valves to select the reversible, irreversible, or mixed mode in opening and closing.
- Twice the rod speed (20mm/s)

#### TECHNICAL INFORMATION

- Absorbed Power: 170W
- Adjustable Force: Hydraulic
- Adjustable Speed: Electronic - Note: When installed in conjunction with the BA230 control board.
- Encoder/Limit Switches: Physical Stops Only
- Frequency of Use: 55%
- Lubrication type: Oil GBD PH-03
- Max. Leaf Width: 3.5m - Note: In the case of solid gates or a leaf width of over 2.5m, a supplementary electric lock is suggested.
- Max. Rod Stroke: 265mm (290mm for the version E)
- Max. Thrust Force: 3000N (2200N for the version ER/S)
- Motor Power Supply: 230Vac - 50/60Hz
- Operating Temp: -20C / +60C
- Protection Level: IP65
- Rod Speed: 10mm/s (20mm/s for version ER/S)
- Type of Use: Heavy Duty
- Weight of Unit: 7.7kg