

GA-TEL-E2K4G



TELGUARD - E2K 4G 2 WAY GSM WITH KEYPAD

Telguard - E2K 4G 2 way GSM with keypad

FEATURES

- 316 marine grade stainless steel faceplate
- 40mm low profile, high strength, anthracite grey alloy cast back box
- LED downlight
- Stainless steel security screws
- Surface mounted
- Downward facing microphone
- THA Horwood quality sound
- Call up to 3 numbers from each call point
- IP64 rated
- Time clock with 3 profiles
- 2 year warranty
- Backlit, vandal resistant keypad
- Timed trade button and clear button
- 100 pin codes for coded entry

Special price £615.00 + VAT

Offer ends 31/12/2023

**** Please call the office to order ****

TECHNICAL INFORMATION

- Power: 12 Volt 1 Amp. DC PSU fitted with a 3A fuse (supplied and must be dedicated to the Telguard intercom unit).
- Power consumption: 120 mA Idle @ 12 Volts.
- Telephone type: Standard DTMF (Dual Tone Multi Frequency) generating telephone, cordless or mobile phone.
- Programming: Remotely programmable via App, SMS or via GSM modem. Locally via USB cable.
- Relays: 3: 1 x 2A, 2 x 200mA, 2 x Auxilliary inputs.
- Relay activation time: 1 - 60 seconds, adjustable locally and remotely
- Operating commands: # Pulses RL1, 1# Pulses RL1, 2# Pulses RL2, 3# Latches RL3, 6# Unlatches RL3
- Time Clocks: This utilizes the on board time clock enabling custom profile functions to be activated.
- Authorised Call Access: 100 telephone numbers can be stored. Calling the unit from an authorised telephone number activates the relay.

