SPECIALIZED SECURITY PRODUCTS

sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

ER310S-24



24VDC ANSI RELEASE SHORT FACEPLATE FAIL SAFE/SECURE

FEATURES

- Ansi style release
- Switchable fail safe / fail secure
- Lip extensions available
- Reversible
- 24Vdc Current consumption with 150mAmp current draw
- Short faceplate suitable for metal doors

- TIP; Fail safe means when the power is cut the door will open, fail secure means when the power is cut the door will remain shut.

TECHNICAL INFORMATION

- Power Input: 12 V DC (24V DC available by special order)
- Voltage Tolerance: 15%
- Current Draw: 0.25 A@12 VDC; 0.15 A@24 VDC at temperature 20
- Sensor Switch: monitored output (optional model)
- Rating 2A@125V, indicates the lockset locked or unlocked status
- Operating Temperature: -10~45
- Humidity: 0~95% non-condensing
- Lock's surface Temperature (when the power is on): <current temperature +20
- 2000lbs jaw strength pull testing
- Tested to 1,000,000 cycles
- Weight: 380g (approx)

RELATED PRODUCTS

			
DU03-CP3LSRC	**ER310-1224**	**LP050**	**SASHFP**