sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

EXT1200




SSP STANDARD MONITORED S/STEEL WEATHERPROOF MAGLOCK 12/24VDC

SSP Standard Monitored S/Steel Weatherproof Maglock 12/24VDC

FEATURES

- Weatherproof
- Lock monitored
- Side and face fixing
- Budget
- Stainless steel
- 12Vdc current consumption with 500mAmp current draw
- 24Vdc current consumption with 250mAmp current draw
- Up to 540kg holding force
- 20mm female conduit fitting



TECHNICAL INFORMATION

- Voltage Tolerance: +/-15%
- Current Draw: 500mA@12Vdc : 250mA@24Vdc
- Magnetic bond sensor monitor output (00R) (SPDT RATED 0.25A@12VDC, remotely monitors the door lock or unlock status of magnet
- Operating Temperature: -10~55C (14~131F)
- Holding Force Up to 1200lbs (545kg)
- Dimensions: Magnet (L)220. (W)62. (D)40mm, Armature: (L)185. (W)62. (D)16.mm
- Epoxy Potting Compound: E87252 (S), UL94V-0
- Weight (approx) : 4.8kg
- IP68 rated

RELATED PRODUCTS



DG500



EM500ZLW



EXT800



SPB008(S)