

## ML350M



### MONITORED FAIL SAFE FIRE RATED ELECTRIC LOCK 12VDC

The ML-350M is ideal for single or double action doors and is suitable for use on emergency escape routes. This electric lock is fire rated and opens when subjected to a side load prior to release.

#### FEATURES

- Fail safe
- Fire rated
- Opens under side pre-load
- Suitable for single or double action doors
- Stainless steel latch and faceplate
- Lock monitoring & door status monitoring
- Vertical or horizontal installation

#### TECHNICAL INFORMATION

- Fire tested in accordance with BS EN 1634-1 : 2014 and BS EN 1363-1: 2012
- Voltage: 12Vdc
- Current draw = 280mA
- Dimensions: 200mm(L) x 25mm(W) x 45mm(D)
- Lock monitoring & door status monitoring
- Monitoring relay contacts rating: 1A@125 VAC
- Pre-load force: up to 227kg
- Operating temp: -10°C to +45°C
- Humidity: 0-95% non condensating
- Long life solenoid tested to 250,000 operations

## RELATED PRODUCTS

 <p><b>ABLOY-EL560DK-SSP</b></p>	 <p><b>GK231M-L</b></p>	 <p><b>ML210</b></p>	 <p><b>ML300</b></p>
---	--	--	---