

**ABLOY-351-U80****12VDC ELECTRIC LOCK FOR SINGLE OR DOUBLE ACTION DOORS 44MM**

12Vdc monitored electric lock designed for single or double action swing doors. Suitable for use on fire route doors the locking bolt is held in the locked position by means of spring power. When the door closes the bolt latches into the striking plate.

**FEATURES**

- Monitoring contact and armature contact integrated
- Sturdy design for demanding requirements

**TECHNICAL INFORMATION**

- Handing: Universal
- Potential: 12Vdc
- Monitoring contact (RR): Yes
- Diode (05): Yes
- Fail-unlocked: Yes
- Rated operating voltage tolerance range:  $12\text{ V} \pm 1\text{ V}$
- Nominal resistance 12V: 37  $\Omega$
- Current consumption DC (stabilized) 12V: 320 mA
- Anchor contact: Yes
- Dead bolt cutout: No
- X measurement: 4,0 - 7,0 mm
- Length: 250 mm
- Thickness: 2 mm
- Break-in resistance: 5000 N
- Height: 200 mm
- Width: 25 mm
- Depth: 42 mm
- Max. latch preload: 5000 N
- Continuous function load: cycles 200000
- Color: Stainless steel

**RELATED PRODUCTS**



**ABLOY-351M.80**



**BGU1G**



**EM02**



**NT200-NS**