sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

ABLOY-351-U80



ABLOY FAIL UNLOCKED ELECTRIC LOCK MONITORED 12V 44MM F/END

Abloy Fail Unlocked Electric Lock for Single or Double Action Doors 12/24Vdc Monitored - 12V 44mm f/end

FEATURES

- Monitoring contact and armature contact integrated
- Sturdy design for demanding requirements

TECHNICAL INFORMATION

- Handing: Universal
- Potential: 12Vdc
- Monitoring contact (RR): Yes
- Diode (05): Yes
- Fail-unlocked: Yes
- Rated operating voltage tolerance range: 12 V ± 1 V
- Nominal resistance 12V: 37 ?
- Current consumption DC (stabilized) 12V: 320 mA
- Anchor contact: Yes
- Dead bolt cutout: No
- X measurement: 4,0 - 7,0 mm
- Length: 250 mm
- Thickness: 2 mm
- Break-in resistance: 5000 N
- Height: 200 mm
- Width: 25 mm
- Depth: 42 mm
- Max. latch preload: 5000 N
- Continuous function load: cycles 200000
- Color: Stainless steel

RELATED PRODUCTS



ABLOY-351M.80



BGU1G



EM02



NT200-NS