sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

ABLOY-EL402



ABLOY SCANDI PROFILE WITH HS DOUBLE ACTION BOLT FAIL LOCKED

Abloy Scandinavian Profile with High Security Double Action Bolt Fail Locked 12/24Vdc

FEATURES

- High security double action bolt
- Fail secure
- Suitable for right or left handed doors
- Suitable for double action doors
- Adjustable back set
- Key/thumb turn override at all times
- Lock monitoring
- Includes EA307 strike plate

TECHNICAL INFORMATION

- Voltage: 12/24 Vdc (-10%/+15%)
- Current draw: 550mA max./240mA idle @ 12 Vdc, 270mA max./110mA idle @ 24 Vdc
- Dimensions: 225mm(L) x 25mm(W)
  Depth: 40-50mm, subject to backset
- Adjustable backset (mm): 25, 28, 30, 33, 35
- Standards: EN 61000-6-3:2007 EMC
  EN 61000-6-1:2007 EMC
  EN 12209:2004 Mechanical resistance
  EN 179:2008 Emergency exit
- The EL402 lock cannot be used in fire doors

RELATED PRODUCTS



ABLOY-EL402-F-UN



CP3



EM10DS



NT200-S-BLUE