

## ABLOY-EL402



### ELECTRO-MECHANICAL FAIL SECURE LOCK FOR NARROW STILE DOORS

The EL402 fail secure is typically used in the exterior doors of apartment buildings and interior doors of business premises. Suitable for double action doors. Mechanical override is possible.

#### FEATURES

- High security double action bolt
- Fail secure
- Suitable for right or left handed doors
- Suitable for double action doors
- Adjustable back set
- Key/thumb turn override at all times
- Lock monitoring
- Includes EA307 strike plate

#### TECHNICAL INFORMATION

- Voltage: 12/24 Vdc (-10%/+15%)
- Current draw: 550mA max./240mA idle @ 12 Vdc, 270mA max./110mA idle @ 24 Vdc
- Dimensions: 225mm(L) x 25mm(W)  
Depth: 40-50mm, subject to backset
- Adjustable backset (mm): 25, 28, 30, 33, 35
- Standards: EN 61000-6-3:2007 EMC  
EN 61000-6-1:2007 EMC  
EN 12209:2004 Mechanical resistance  
EN 179:2008 Emergency exit
- The EL402 lock cannot be used in fire doors

## RELATED PRODUCTS



**ABLOY-EL402-F-UN**



**CP3**



**EM10DS**



**NT200-S-BLUE**