sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

ABLOY-EL402-F-UN



ABLOY SCANDI PROFILE HS DOUBLE ACTION BOLT FAIL UNLOCKED

Abloy Scandinavian Profile with High Security Double Action Bolt Fail Unlocked 12/24Vdc

FEATURES

- Fail-unlocked (Fail-safe)
- Suitable for right or left handed doors
- Suitable for double action doors
- Adjustable backset
- Lock monitoring
- Manual override is possible with suitable key cylinder or push pad
- Includes EA307 strike plate

TECHNICAL INFORMATION

- Voltage: 12/24 Vdc (-10%/+15%)
- Current draw: 550mA max./240mA idle @ 12 Vdc
  270mA max./110mA idle @ 24 Vdc
- Adjustable backset (mm): 25, 28, 30, 33, 35
- Dimensions: 225mm(L) x 25mm(W)
  Depth: 40-50mm, subject to backset
- Standards: EN 61000-6-3:2007 EMC
  EN 61000-6-1:2007 EMC
  EN 12209:2004 Mechanical resistance
  EN 179:2008 Emergency exit
- The EL402 F-UN lock cannot be used in fire doors

RELATED PRODUCTS



ABLOY-351-U80



ABLOY-EL402



CP3-LSRC



EM20