

## ABLOY-EL402-F-UN



### ELECTRO-MECHANICAL FAIL SAFE LOCK FOR NARROW STILE DOORS

The EL402-F-UN fail safe is typically used in the exterior doors of apartment buildings and interior doors of business premises. Suitable for double action doors. Mechanical override is possible.

#### FEATURES

- Fail-unlocked (Fail-safe)
- Suitable for right or left handed doors
- Suitable for double action doors
- Adjustable backset
- Lock monitoring
- Manual override is possible with suitable key cylinder or push pad
- Includes EA307 strike plate

#### TECHNICAL INFORMATION

- Voltage: 12/24 Vdc (-10%/+15%)
- Current draw: 550mA max./240mA idle @ 12 Vdc  
270mA max./110mA idle @ 24 Vdc
- Adjustable backset (mm): 25, 28, 30, 33, 35
- Dimensions: 225mm(L) x 25mm(W)  
Depth: 40-50mm, subject to backset
- Standards: EN 61000-6-3:2007 EMC  
EN 61000-6-1:2007 EMC  
EN 12209:2004 Mechanical resistance  
EN 179:2008 Emergency exit
- The EL402 F-UN lock cannot be used in fire doors

## RELATED PRODUCTS



**ABLOY-351-U80**



**ABLOY-EL402**



**CP3-LSRC**



**EM20**