

FAAC-KIT-770-24V



770 24V SWING ARM GATE DOUBLE KIT FOR GATES UP TO 3.5M

FAAC 770 24V KIT for a pair of residential swing gates up to a maximum of 3.5m each leaf.

FEATURES

- Protection class: IP67
 - To “initialise” the automated system, just carry out the SET-UP operation, selecting a suitable dipswitch
 - The following parameters are automatically self-learned during this operation:
 - Opening/closing times
 - Pause time
 - Traction/thrust force
 - Deceleration at end of opening and closing
 - Soft start (starting at gradual speed)
 - Continuously controlled electronic clutch, active at both opening and closing
 - Four sensitivity levels
 - Movement reversed in case of an obstacle
 - Emergency stop function (if clutch operates for two consecutive cycles)
 - Emergency battery (optional) ensuring operation during a power cut (15 cycles max)
-
- Kit includes:
 - 2x FAAC 770 24V Electromechanical Operator
 - 2x Underground Foundation box with release System
 - 1x FAAC E024S Control Board
 - 1x Control Board Housing
 - 1x Pair of FAAC XP20B photocells
 - 1x FAAC Plug-in Receiver / Decoder 868 SLH
 - 2x FAAC Two Channel Transmitter 868 SLH