


RT-BE20/200



QUICK W	QUICK W	ANGULO
mm	mm	APERTURA
110	100	140°
110	200	90°
120	100	140°
120	200	140°
130	100	140°
130	130	120°
130	150	110°
150	200	140°
160	130	110°
160	150	140°
QUICK W	QUICK W	QUICK W
860 mm	860 mm	mm
100	200	90

BRUSHLESS MOTOR FOR SWING GATES UP TO 2.8M

Low voltage brushless electromechanical actuator, for super intensive use, with native encoder on board, irreversible, ideal for swing gates with leaves up to 2.8m with mechanical stops on opening and closing.

FEATURES

- Electromechanical actuator BRUSHLESS
- Low voltage
- Super intensive use, with native encoder onboard
- Irreversible
- Ideal for swing gates with leaf up to 2.8m length, with mechanical stopper in opening and closing

TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 24V
- Power rating: 200W
- Frequency of use: Intensive use
- Thrust: 100 - 2200N
- Operating temperature: -20 C° +55 C°
- Protection level: IP43
- Reductor Type: Irreversible
- Manoeuvre speed: 1.66 cm/s
- Opening time at 90°: 15-25 s
- Stroke: 400 mm
- Limit switch: Mechanical stopper in opening and closing
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Operating cycles per day (opening/closing - 24 hours no stop): 800
- Maximum dimension product in mm (L x W x H): 867 x 105 x 155
- Product weight packed (Kg): 7.9

RELATED PRODUCTS



RT-BE20/200/HS



RT-MC781



RT-KT206