Abloy Oy Wahlforssinkatu 20 P.O. Box 108 FI-80101 Joensuu, Finland | Tel. +358 20 599 2501 | abloy.com





ABLOY[®] CY326 **DIN single cylinder**

Product description

High durability cylinder against pulling, twisting and sawing.

- Overview of Advantages Can be use with wide range applications for DIN cylinders Suitable for both outer and inner door use
- Adjustable length with extension system to match different door thicknesses
 Adjustable locked position of cam
- Several plating options





Technical data	
Available key systems	ABLOY PROTEC, ABLOY PROTEC ² , ABLOY NOVEL
Available plating options	Bright chrome (Cr), Satin chrome (HCr), Brushed nickel (NiHa), Bright brass (MSKiLa), Satin brass (MSHaLa)
Cylinder length	36mm
Length adjustable	with 5mm steps 36–86mm, and with 10mm steps 86–136mm
Weight	0,17kg

This content is protected by Intellectual Property Rights Laws. The title to the content shall not pass to you, and instead shall remain with Abloy Oy or a third party holding the title. Abloy develops continuously the products and solutions offered. Therefore, the information contained in the document is subject to change without notice. ABLOY PROVIDES THIS CONTENT ON AN "AS IS" BASIS WITHOUT ANY WARRANTIES OF ANY KIND, EXPRESS, IMPLIED, OR STATUTORY."

